

K 1300 R

BMW Motorrad
Roadster



K 1300 R

The Ultimate
Riding Machine



Sapphire Black Metallic / Black Satin Gloss

TECHNICAL DATA

Type

Water-cooled 4-stroke in-line four-cylinder engine, two overhead camshafts, four valves per cylinder

Fuel Type

Unleaded super and premium, octane number 95-98 (RON) (knock sensor; rated output at 98 RON)

Capacity

1,293 cc

Rated Output

127 kW (173 hp) at 9,250 rpm

Max torque (Nm/rpm)

140 Nm at 8,250 rpm

Fuel consumption (l/100km)

5.0 l

Manufacturer Recommended Nett Selling Price

RM 114,455.00

Road Tax 1 Year (Personal)

RM 350.00

Registration Fee

RM 5.00

Inspection Fee

RM 70.00

Ownership Claim

RM 20.00

OTR Retail Price without Insurance Inclusive 6% GST

RM 114,900.00

Actual motorcycle specifications may vary from the picture shown above.

OTR price is effective 16 April 2015, based on Manufacturer Recommended Nett Selling Price, and only valid in Peninsular Malaysia.

OTR price is inclusive of 6% GST.

Prices and specifications are subject to change without prior notice.

BMW Credit recommends BMW Comprehensive Motor Insurance.



BMW Motorrad Authorised Dealers

- **AUTO BAVARIA** - Glenmarie 3A, Persiaran Kerjaya, Seksyen U1 Glenmarie, 40150 Shah Alam, Selangor Darul Ehsan. Tel: 03-5566 3843 Penang 15, Jalan Anson, 10400 Pulau Pinang. Tel: 04-238 7888
- **CHEAR MOTORRAD** - Puchong No.84, Jalan Suria Puchong 1, Pusat Perniagaan Suria Puchong, 47100 Puchong, Selangor. Tel: 03-8940 1618/1318 Kuantan No. 46, 46A, Jalan Putra Square 6, Putra Square, 25200 Kuantan, Pahang Darul Makmur. Tel: 09-5134 140 / 09-5134 210
- **TIAN SIANG PREMIUM AUTO** - Ipoh No.99, Jalan Tunku Abdul Rahman, 30010 Ipoh, Perak Darul Ridzuan. Tel: 05-506 2800/2100 Langkawi Plot 67-68, Persiaran Dayang 1, Dayang Business Centre, 07000 Kuah, Langkawi, Kedah. Tel: 04-966 8628 Fax: 04-966 8698
- **FM AUTOHAUS SDN BHD** Lot 17362 Mile 3, Jalan Penampang, 88300 Kota Kinabalu, Sabah. Tel: 088 - 703 492 Fax: 088 - 703 686
- **WEARNES AUTOHAUS SDN BHD** 3B, (PTD 158193) Jalan Persiaran Desa Tebrau, Taman Desa Tebrau, 81100 Johor Bahru, Johor. Tel: 07 - 361 9888 Fax: 07 - 361 9988
- **REGAS PREMIUM AUTO SDN BHD** No. 8, Jalan Tun Jugah, 93350 Kuching, Sarawak. Tel: 082 - 467 777 Fax: 082 - 467 788

K 1300 R

TECHNICAL DATA

Engine:

Type	: Water-cooled 4-stroke in-line four cylinder engine, two overhead camshafts, four valves per cylinder
Bore / stroke	: 80 mm x 64,3 mm
Capacity	: 1,293 cc
Rated output	: 127 kw at 9,250 rpm
Max. torque	: 140 Nm at 8,250 rpm
Compression ratio	: 13.0 : 1
Mixture control / engine management	: Electronic intake pipe injection / digital engine management including knock sensor (BMS-K+)
Emission control	: Closed-loop 3-way catalytic converter, emission standard EU-3

Performance / Fuel Consumption:

Maximum speed	: over 200 km/h
Fuel consumption per 100 km at constant 90 km/h	: 5.0 l
Fuel consumption per 100 km at constant 120 km/h	: 5.8 l
Fuel type	: Unleaded super, octane number 95-98 (RON) (knock sensor; rated output at 98 RON)

Electrical System:

Alternator	: Three-phase alternator 580 W
Battery	: 12 V / 12 Ah, maintenance-free

Power Transmission:

Clutch	: Multiple-disc clutch in oil bath, hydraulically operated
Gearbox	: Constant mesh 6-speed, gearbox
Drive	: Shaft drive

Chassis / Brakes:

Frame	: Bridge-type frame, cast aluminium, load-bearing engine
Front wheel location / suspension	: BMW Motorrad Duolever; central spring strut

Rear wheel location / suspension

: Cast aluminium single-sided swing arm with BMW Motorrad Paralever; central spring strut with lever system, spring pre-load hydraulically adjustable (continuously variable) at handwheel, rebound damping adjustable

Suspension travel front/rear

: 115mm /135 mm

Wheelbase

: 1,585 mm

Castor

: 104.4 mm

Steering head angle

: 60.4°

Wheels

: Cast aluminium wheels

Rim front

: 3.50 x 17"

Rim rear

: 5.50 x 17"

Tyres front

: 120/70 ZR 17

Tyres rear

: 180/55 ZR 17

Brake front

: Dual disc brake, diameter 320 mm, 4-piston fixed calipers

Brake rear

: Single disc brake, diameter 265 mm, double-piston floating caliper

ABS

: Standard

Dimensions / Weight:

Length : 2,228 mm

Height (not inc. mirrors) : 1,095 mm

Width (inc. mirrors) : 856 mm

Seat height, unladen weight : 820 mm

Inner leg curve : 1,810 mm

Unladen weight, road ready, fully fuelled 1) : 243 kg

Dry weight 2) : 217 kg

Permitted total weight : 460 kg

Payload (with standard equipment) : 217 kg

Usable tank volume : 19 l

Reserve : Approx. 4.0 l

Technical data related to the unladen weight (DIN)

1) According to guideline 93/93/EEC with all fluids, fuelled with at least 90% of usable tank volume

2) Unladen weight without fluids (without panniers)