

K 1600 GTL EXCLUSIVE

BMW Motorrad
Tour



K 1600 GTL
Exclusive

The Ultimate
Riding Machine



Mineral White Metallic

TECHNICAL DATA

Type

Oil / Water-cooled 4-stroke in-line
6-cylinder engine, four valves
per cylinder, two overhead
camshafts

Fuel Type

Unleaded super, octane
number 95 (RON)

Capacity

1,649 cc

Rated Output

118 kW (160 hp) at 7,750 rpm

Max torque (Nm/rpm)

175 Nm at 5,250 rpm

Fuel consumption (ltr/100km)

4.6 l

Manufacturer Recommended Nett Selling Price

RM 185,455.00

Road Tax 1 Year (Personal)

RM 350.00

Registration Fee

RM 5.00

Inspection Fee

RM 70.00

Ownership Claim

RM 20.00

OTR Retail Price without Insurance Inclusive 6% GST

RM 185,900.00

Actual motorcycle specifications may vary from the picture shown above.

OTR price is effective 16 April 2015, based on Manufacturer Recommended Nett Selling Price, and only valid in Peninsular Malaysia.

OTR price is inclusive of 6% GST.

Prices and specifications are subject to change without prior notice.

BMW Credit recommends BMW Comprehensive Motor Insurance.



BMW Motorrad Authorised Dealers

- **AUTO BAVARIA** - Glenmarie 3A, Persiaran Kerjaya, Seksyen U1 Glenmarie, 40150 Shah Alam, Selangor Darul Ehsan. Tel: 03-5566 3843 Penang 15, Jalan Anson, 10400 Pulau Pinang. Tel: 04-238 7888
- **CHEAR MOTORRAD** - Puchong No.84, Jalan Suria Puchong 1, Pusat Perniagaan Suria Puchong, 47100 Puchong, Selangor. Tel: 03-8940 1618/1318 Kuantan No. 46, 46A, Jalan Putra Square 6, Putra Square, 25200 Kuantan, Pahang Darul Makmur. Tel: 09-5134 140 / 09-5134 210
- **TIAN SIANG PREMIUM AUTO** - Ipoh No.99, Jalan Tunku Abdul Rahman, 30010 Ipoh, Perak Darul Ridzuan. Tel: 05-506 2800/2100 Langkawi Plot 67-68, Persiaran Dayang 1, Dayang Business Centre, 07000 Kuah, Langkawi, Kedah. Tel: 04-966 8628 Fax: 04-966 8698
- **FM AUTOHAUS SDN BHD** Lot 17362 Mile 3, Jalan Penampang, 88300 Kota Kinabalu, Sabah. Tel: 088 - 703 492 Fax: 088 - 703 686
- **WEARNES AUTOHAUS SDN BHD** 3B, (PTD 158193) Jalan Persiaran Desa Tebrau, Taman Desa Tebrau, 81100 Johor Bahru, Johor. Tel: 07 - 361 9888 Fax: 07 - 361 9988
- **REGAS PREMIUM AUTO SDN BHD** No. 8, Jalan Tun Jugah, 93350 Kuching, Sarawak. Tel: 082 - 467 777 Fax: 082 - 467 788

K 1600 GTL EXCLUSIVE

TECHNICAL DATA

Engine:

Type	: Oil / Water-cooled 4-stroke in-line two-cylinder engine, four valves per cylinder, two overhead camshafts
Bore / stroke	: 72 mm x 67.5 mm
Capacity	: 1,649 cc
Rated output	: 118 kw (160hp) at 7,750 rpm
Max. torque	: 175 Nm at 5,250 rpm
Compression ratio	: 12.2 : 1
Mixture control / engine management	: Electronic intake pipe injection
Emission control	: Closed-loop 3-way catalytic converter, emission standard EU-3

Performance / Fuel Consumption:

Maximum speed	: over 200 km/h
Fuel consumption per 100 km at constant 90 km/h	: 4.6 l
Fuel consumption per 100 km at constant 120 km/h	: 5.9 l
Fuel type	: Unleaded super, octane number 95 (RON)

Electrical System:

Alternator	: Three-phase alternator 580 W
Battery	: 12 V / 19 Ah, maintenance-free

Power Transmission:

Clutch	: Multiple-disc clutch in oil bath
Gearbox	: 6-speed, helical, gearbox
Drive	: Shaft drive

Chassis / Brakes:

Frame	: Bridge-type frame, cast aluminium, load-bearing engine
Front wheel location / suspension	: BMW Motorrad Duolever; central spring strut

Rear wheel location / suspension	: BMW Motorrad Paralever
Suspension travel front/rear	: 125 mm / 135 mm
Wheelbase	: 1,618 mm
Castor	: 108.4 mm
Steering head angle	: 62.2°
Wheels	: Cast aluminium wheels
Rim front	: 3.50 x 17"
Rim rear	: 6.00 x 17"
Tyres front	: 120/70 ZR 17
Tyres rear	: 190/55 ZR 17
Brake front	: Dual disc brake, diameter 320 mm, 4-piston fixed calipers
Brake rear	: Single disc brake, diameter 320 mm, double-piston caliper
ABS	: BMW Motorrad Integral ABS (part-integral)

Dimensions / Weight:

Length	: 2,489mm
Height (not inc. mirrors)	: 1,465 mm
Width (inc. mirrors)	: 1,000 mm
Seat height, unladen weight	: 750 mm (OE seat extra high: 800mm)
Inner leg curve	: 1,720 mm (OE seat extra high: 1,810mm)
Unladen weight, road ready, fully fuelled 1)	: 360 kg
Permitted total weight	: 560 kg
Payload (with standard equipment)	: 196 kg
Usable tank volume	: 26.5 l
Reserve	: Approx. 4.0 l

Technical data related to the unladen weight (DIN)

1) According to guideline 93/93/EEC with all fluids, fuelled with at least 90% of usable tank volume